



PIN ASSIGNMENT:

PIN	SYMBOL
1	CSB
2	RSTB
3	A0
4	D6
5	D7
6	VDD
7	VSS
8	VOOUT
9	XV0in
10	NC
11	NC
12	VGIN
13	LEDA
14	LEDK

6 O'CLOCK VIEWING DIRECTION

DETAIL A  
SCALE 10:1

- NOTES:
- 1.DISPLAY TYPE: DFSTN
  - 2.VIEW DIRECTION: 6 O'CLOCK
  - 3.POLARIZER TYPE: TRANSLLECTIVE/POSITIVE
  - 4.DRIVER METHOD: 1/64 DUTY 1/9 BIAS
  - 5.LCD DRIVING VOLTAGE: 8.0V
  - 6.LOGIC SUPPLY VOLTAGE: 3.3V
  - 7.OPERATING TEMP: -20°C~+70°C
  - 8.STORAGE TEMP: -30°C~+80°C
  - 9.CONNECTOR TYPE: COG+FPC
  - 10.CONTROLLER/DRIVE IC: ST7567
  - 11.BACKLIGHT: WHITE

DRIVER METHOD [VLED=3.0±0.3V, ILED=30mA]

AMEND		SUNLIKE DISPLAY TECH. CORP.								
		APPROVALS		DATE	PROJECTION		VERSION			
△B		APP			◎		AMG128064B			
△A	NEW	CHK	2015.11.24		◎		A			
NO.	CONTENT	DWN	DATE		15.12.18	PROJECTION	VERSION	A	UNIT: MM	NO.1/1