



PIN ASSIGNMENT:

NO	PIN
1	CS1
2	RST
3	A0
4	WR
5	RD
6	D0
7	D1
8	D2
9	D3
10	D4
11	D5
12	D6
13	D7
14	VDD
15	VSS
16	NC
17	NC
18	VO
19	XV0
20	NC
21	NC
22	VG
23	NC
24	NC
25	NC
26	NC
27	NC
28	C86
29	PS
30	NC

NOTES:

- 1.DISPLAY TYPE: STN/BLUE
- 2.VIEW DIRECTION: 6 O'CLOCK
- 3.POLARIZER TYPE: TRANSMISSIVE/NEGATIVE
- 4.DRIVER METHOD: 1/65 DUTY 1/9 BIAS
- 5.LCD DRIVING VOLTAGE: 8.5V
- 6.LOGIC SUPPLY VOLTAGE: 3.3V
- 7.OPERATING TEMP: 0°C~+55°C
- 8.STORAGE TEMP: -10°C~+70°C
- 9.CONNECTOR TYPE: COG+FPC
- 10.CONTROLLER/DRIVE IC: ST7567
- 11.BACKLIGHT: WHITE

DRIVER METHOD [VLED=3.0±0.3V, ILED=45mA]

No Line marking on LCD protective film.  
LCD上保护膜表面不需划线

DOTS DETAIL  
SCALE 5:1

AMEND		SUNLIKE DISPLAY TECH. CORP.								
		APPROVALS		DATE	PROJECTION		AMG128064G			
△	NEW			17.01.18	APP		CHK			
NO.	CONTENT			DATE	DWN	XXJ		17.01.18	VERSION	A
									UNIT: MM	NO.1/1