



NOTES:

- 1.DISPLAY TYPE: FSTN/GRAY
- 2.VIEW DIRECTION: 6 O'CLOCK
- 3.POLARIZER TYPE: TRANSPARENT/POSITIVE
- 4.DRIVER METHOD: 1/33 DUTY 1/6 BIAS
- 5.LCD DRIVING VOLTAGE: 8.0V
- 6.LOGIC SUPPLY VOLTAGE: 3.0V
- 7.OPERATING TEMP: -10°C~+60°C
- 8.STORAGE TEMP: -20°C~+70°C
- 9.CONNECTOR TYPE: COG+PIN
- 10.CONTROLLER/DRIVE IC: ST7565R

BACK

PIN ASSIGNMENT:

1	2	3	4	5	6	7	8	9	10	11	12	13	14
CS	RST	A0	WR	RD	D0	D1	D2	D3	D4	D5	D6	D7	VDD
15	16	17	18	19	20	21	22	28	24	25	26	27	28
VSS	VOUT	CAP3P	CAP1N	CAP1P	CAP2P	CAP2N	V4	V3	V2	V1	V0	C86	PSB

SUNLIKE DISPLAY TECH.CORP.

APPROVALS

DATE

AMG128032C

CHANGE PIN STYLE

2015.12.04

APP

2015.11.04

CHK

PROJECTION

VERSION A UNIT:MM NO.1/1

NO.

CONTENT

DATE

DWN

2015.11.04

CHK

PROJECTION

VERSION A UNIT:MM NO.1/1