


↻ 6 O'CLOCK VIEWING DIRECTION



DOTS SIZE:10/1

- NOTES:
- 1.DISPLAY TYPE: FSTN
 - 2.VIEW DIRECTION: 6 O'CLOCK
 - 3.POLARIZER TYPE: TRANSMISSIVE/NEGATIVE
 - 4.DRIVER METHOD: 1/65 DUTY 1/9 BIAS
 - 5.LCD DRIVING VOLTAGE: 9.0V
 - 6.LOGIC SUPPLY VOLTAGE: VDD1:1.8V VDD2:2.8V
 - 7.OPERATING TEMP: -20°C~+70°C
 - 8.STORAGE TEMP: -30°C~+80°C
 - 9.CONNECTOR TYPE: COG+FP+C+B/L
 - 10.CONTROLLER/DRIVE IC: ST7567S
 - 11.BACKLIGHT: WHITE, 1pcs, Vf=2.8v If≤15mA
 - 12.OTHER TOLERANCE: ±0.2mm

PIN NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17
SYMBOL	NC	NC	NC	NC	NC	NC	NC	VSS	V10-1V8	NC	NC	NC	CSB	RSTB	AO	NC	NC
PIN NO.	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	
SYMBOL	SCL	SDA	NC	VSS	VSS	NC	NC	NC	NC	NC	NC	NC	NC	VDD2_8	LBCK-	LBCK+	

AMEND		SUNLIKE DISPLAY TECH. CORP.		LCM DRAWING	
NO.	CONTENT	DATE	CHK	PROJECTION	VERSION
Δ	NEW	2015.08.26	CHK	Orthographic	AMG128064A
					UNIT: MM NO.1/1